



Ratings and Dimensions

Voltage	Model	Max. Full Load Amps	Rated HP (Approx.)	W	H	D	W1	H1	d	Wt/ lbs	Total Heat Loss (@ 2 kHz)
				Dimensions in inches							
230V	2002-T	1.9	¼	2.7	5.0	3.0	2.2	4.6	M4	1.3	17.1
	2004-T	3.5	½ & ¾	2.7	5.0	4.3	2.2	4.6	M4	2.0	29.4
	2006-T	6.0	1 & 1½	2.7	5.0	5.0	2.2	4.6	M4	2.4	44.7
	2010-T	9.6	2 & 3	4.3	5.0	5.1	3.8	4.6	M4	3.8	77.5
	2012-T	12.0	3	4.3	5.0	5.4	3.8	4.6	M4	3.8	91.7
460V	4001-T	1.2	½	4.3	5.0	3.2	3.8	4.6	M4	2.2	19.6
	4002-T	2.1	¾ & 1	4.3	5.0	3.9	3.8	4.6	M4	2.7	32.4
	4004-T	4.1	2	4.3	5.0	5.4	3.8	4.6	M4	3.8	47.3
	4005-T	5.4	3	4.3	5.0	6.1	3.8	4.6	M4	3.8	66.3
	4009-T	8.8	5	4.3	5.0	6.1	3.8	4.6	M4	3.8	95.1



